


# Product data sheet

NEO EQUINOX CLAMP  
7715-I-5-667-XX  
UNILAMP



EQUINOX is the trapeze-shaped extendable light fixture for residential and public space. It is operated with LED light source. It can be used on a pole with a clamping unit and also as a wall mounted fixture. With high quality LED chips from world renowned manufacturer, EQUINOX is an economical luminaire that provides general illumination with fantastic lighting levels. There is no light spill above the horizontal when the luminaire is positioned perpendicular to the pole or wall. The IP rated clip-lock system enable EQUINOX to be used in an outdoor environment without any ingress of harmful dust and water. High efficiency lenses allow Equinox to perform brilliantly and efficiently. Extruded aluminium and/or galvanized steel pole and anchor unit for concrete foundation are also available. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Molded Lens from renowned manufacturer. • Adjustable optic. • GFR PA6.6 Terminal block. • M20 cable gland/ weather proof TPE grommet. Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x LED			
Nominal lamp power	32 W	LOR	88%
Lamp flux	6080 lm	Total flux	5339 lm
Luminous efficacy	190 lm/W	Total power	36 W
CCT	4000 K		
CRI	80		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 5.87 in  
Width: 31.97 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 36 W  
Controller: DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 07