



Product data sheet

167 G2 LUXANO 2 LED DAMP-PROOF LIGHT FITTING
167 12L42G2 LW DV P5X2,5 (16702 1013)
SCHUCH



LED damp-proof light fitting, LUXANO 2, 23 W, 4000 lm, 174 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI \geq 80, Ta -20 °C/+35 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Stainless steel (1.4310), Housing Glass fibre reinforced polyester, Colour grey, Through wiring (DV) 5x2.5 mm² PVC, for agricultural farms. LED damp-proof light fitting LUXANO 2 for application in stables and animal husbandry. Glass fibre reinforced polyester housing, frosted diffuser, foamed gasket and stainless steel clips. Powder-coated reflector with special highly resistant LED modules and encapsulated ECG, variable cable entry and stainless steel mounting clips for quick and easy mounting. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1185,00 mm, Width/Diameter 85,00 mm, Height 88,00 mm, Net weight 1,82 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	4001 lm	LOR	100%
Luminous efficacy	174 lm/W	ULOR	7%
		Total power	23 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 46.65 in
Width: 3.35 in
Height: 3.46 in

Adjustability

Fixed

Electric

System power: 23 W
Appliance Class: I

Protection

IP: 65
IK: 05
Designation labels: CE