

# Product data sheet


GEORG V (1-ARMED)  
9.870.0126.04  
LEIPZIGER LEUCHTEN



IP  
54

With mounting heights between 3.00 and 4.00 m for medium and low light requirements. - Large shade, inside in special white paint for better reflection - Luminaire body made of aluminium/galvanized steel sheet, outside painted in colour, inside finished in special white pain - Impact-resistant polyethylene attachment rotates and locks into place for easy lamp replacement - Steel tubing galvanized and painted -Wired ready for connection - Connetion by adapter jack -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm,and pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	24 lm/W
CCT	3400 K
CRI	54

LOR	72%
ULOR	4%
Total flux	1437 lm
Total power	59 W



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	32 lm/W
CCT	3400 K
CRI	54

LOR	72%
ULOR	4%
Total flux	2875 lm
Total power	89 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 28.35 in

Diameter: 22.83 in

## Electric

System power: 59-89 W

## Protection

IP: 54