

Product data sheet

LED DOWNLIGHTS
V1-R0-00819-20D01-2002430 DL-BOX OPAL 140X140 24W 3000K DALI
VARTON




IP
20

IK
01

Cube-shaped surface-mounted downlight. Paintable in any RAL color. Application: offices, commercial spaces, hospitality (restaurants, hotels, coffee bars), retail spaces. Installation: surface-mounted. Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YXJ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP20 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-box-opal/dl-box-opal-140kh140-nakladnye/svetodiodnyy-svetilnik-var-ton-dl-box-nakladnoy-24-vt-3000-k-140x140x170-mm-ral9003-belyy-muar-s-rass_1/

Light output 1



1 x LED			
Nominal lamp power	24 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	92 lm/W	Total power	24 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 24 W

Shape and measurements

Length: 5.51 in

Width: 5.51 in

Height: 6.69 in

Protection

IP: 20

IK: 01

Adjustability

Fixed