Product data sheet


MASTAUSLEGERLEUCHTE SERA-2 ZWEIFACH ASY13 32LED 2700K
88.09900.0V00X + 99.30000.0V00X
HESS



IP 65 IK 09


Auf-/Ansatzleuchte Sera-2 Leuchten Gehäuse aus Aluminium-Druckguss Ausladung Mastachse bis Leuchtenspitze 650 mm Leuchten Abdeckung aus Einscheibensicherheitsglas (IK09), bedruckt Neigungswinkel Ansatzmontage 0°/-15° in 5° Schritten Mit elektronischem Vorschaltgerät (220-240V/50-60Hz) ISchutzart IP66 Ausleger 2-fach gefertigt aus Stahl, verzinkt Leuchtenanschluss seitlich angesetzt an gebogenem Rohr Neigung 20° Ausladung 2 x 500 mm

Light output 1




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3935 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	3935 lm
CCT	2700 K	Total power	33.9 W
CRI	80		




1 x LED

Nominal lamp power	65.9 W	LOR	100%
Lamp flux	7474 lm	ULOR	100%
Luminous efficacy	113 lm/W	Total flux	7474 lm
CCT	2700 K	Total power	65.9 W
CRI	80		




1 x LED

Nominal lamp power	61.3 W	LOR	100%
Lamp flux	6994 lm	ULOR	100%
Luminous efficacy	114 lm/W	Total flux	6994 lm
CCT	2700 K	Total power	61.3 W
CRI	80		




1 x LED

Nominal lamp power	56.7 W	LOR	100%
Lamp flux	6509 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	6509 lm
CCT	2700 K	Total power	56.7 W
CRI	80		




1 x LED

Nominal lamp power	52.2 W	LOR	100%
Lamp flux	6013 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	6013 lm
CCT	2700 K	Total power	52.2 W
CRI	80		




1 x LED

Nominal lamp power	47.6 W	LOR	100%
Lamp flux	5512 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	5512 lm
CCT	2700 K	Total power	47.6 W
CRI	80		




1 x LED

Nominal lamp power	38.5 W	LOR	100%
Lamp flux	4475 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	4475 lm
CCT	2700 K	Total power	38.5 W
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3384 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	3384 lm
CCT	2700 K	Total power	29.4 W
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2838 lm	ULOR	100%
Luminous efficacy	114 lm/W	Total flux	2838 lm
CCT	2700 K	Total power	24.8 W
CRI	80		



1 x LED


Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2282 lm	ULOR	100%
Luminous efficacy	113 lm/W	Total flux	2282 lm
CCT	2700 K	Total power	20.2 W
CRI	80		



1 x LED


Nominal lamp power	43 W	LOR	100%
Lamp flux	4999 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	4999 lm
CCT	2700 K	Total power	43 W
CRI	80		

Light output 2




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2838 lm	ULOR	100%
Luminous efficacy	114 lm/W	Total flux	2838 lm
CCT	2700 K	Total power	24.8 W
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2282 lm	ULOR	100%
Luminous efficacy	113 lm/W	Total flux	2282 lm
CCT	2700 K	Total power	20.2 W
CRI	80		




1 x LED

Nominal lamp power	38.5 W	LOR	100%
Lamp flux	4475 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	4475 lm
CCT	2700 K	Total power	38.5 W
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3384 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	3384 lm
CCT	2700 K	Total power	29.4 W
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3935 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	3935 lm
CCT	2700 K	Total power	33.9 W
CRI	80		




1 x LED

Nominal lamp power	65.9 W	LOR	100%
Lamp flux	7474 lm	ULOR	100%
Luminous efficacy	113 lm/W	Total flux	7474 lm
CCT	2700 K	Total power	65.9 W
CRI	80		




1 x LED

Nominal lamp power	61.3 W	LOR	100%
Lamp flux	6994 lm	ULOR	100%
Luminous efficacy	114 lm/W	Total flux	6994 lm
CCT	2700 K	Total power	61.3 W
CRI	80		




1 x LED

Nominal lamp power	56.7 W	LOR	100%
Lamp flux	6509 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	6509 lm
CCT	2700 K	Total power	56.7 W
CRI	80		




1 x LED

Nominal lamp power	52.2 W	LOR	100%
Lamp flux	6013 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	6013 lm
CCT	2700 K	Total power	52.2 W
CRI	80		



1 x LED

Nominal lamp power	47.6 W	LOR	100%
Lamp flux	5512 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	5512 lm
CCT	2700 K	Total power	47.6 W
CRI	80		



1 x LED

Nominal lamp power	43 W	LOR	100%
Lamp flux	4999 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	4999 lm
CCT	2700 K	Total power	43 W
CRI	80		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 40.22 in
Width: 3.50 in
Height: 10.74 in

Adjustability

Tiltable

Electric

System power: 40.4-131.8 W

Protection

IP: 65
IK: 09