



# Product data sheet

ALU-SUPERIOR  
51063.0031  
RZB



Series: Alu-Superior Type of Protection: IP 65 Protection Class: I Voltage: 230 V / 50 - 60 Hz Base and protective cage: die-cast aluminium, powder-coated. Diffuser: plastic (polycarbonate), opal. Available Colours: anthracite metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 245, H 125 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 350lm System power: 9W Beam Angle: 121° Number of fittings B10A: 30 Number of fittings B16A: 50 Inrush current: 5A Unified Glare Ratio: 18,1 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	350 lm	LOR	100%
Luminous efficacy	39 lm/W	ULOR	12%
		Total power	9 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 4.92 in  
Diameter: 9.65 in

## Adjustability

Fixed

## Electric

System power: 9 W

## Protection

IP: 65  
IK: 08