


Product data sheet

BASIC AFL TR 1000 840 MD WH
EL10810923
ESYLUX



LED floodlight with compact aluminium housing for unobtrusive installation Control system: ON/OFF Installation type: Surface mounting
Installation position: Wall Dimensions: Length 160 mm x Width 170 mm x Height/Depth 58 mm Weight: 523 g Protection type: IP65
ApplianceClass: Class I Permissible ambient temperature: -25 °C...+40 °C Colour: white, similar to RAL 9016 Nominal voltage: 220 - 240 V AC /
50 - 60 Hz TotalSystemPower: 10 W Luminous flux: 1000 lm Luminous efficacy: 100 lm/W Colour temperature: 4100 K Colour rendering index
R_a: > 80 Rated lifetime L_B50 at 25 °C: 40000 h<p/>ArticleNumber: EL10810923
<https://www.esylux.com/p/EL10810923>

Light output 1



1 x LED			
Nominal lamp power	9.8 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	102 lm/W	Total power	9.8 W
CCT	4100 K		
CRI	81		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.33 in
Width: 6.18 in
Height: 1.18 in

Adjustability

Tiltable

Design

Color of housing: White

Electric

System power: 9.8 W
Appliance Class: I

Protection

IP: 65