



# Product data sheet

PRO-SPACE S 155X155MM  
4000429X  
PROLUMIA




Light source: SMD LED Beam angle: 120° Color rendering: Ra >80 Operating temperature: -25°C - +50°C Rated life hours: > 50,000 LED driver (included): CE Input: 220 - 240V AC 50Hz Safety class: Class II

## Light output 1




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1160 lm	Total flux	1160 lm
Luminous efficacy	77 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1210 lm	Total flux	1210 lm
Luminous efficacy	81 lm/W	Total power	15 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1100 lm	Total flux	1100 lm
Luminous efficacy	73 lm/W	Total power	15 W
CCT	2700 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 15 W  
Appliance Class: I

### Shape and measurements

Length: 6.10 in

Width: 6.10 in

Height: 0.79 in

### Protection

IP: 66

IK: 08

Designation labels: CE