Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-70638-04L05-6525050 OLYMP 2.0 GL 250 W 250W 5000K LAMBERT
VARTON



IP 65 IK 08

Medium-power Industrial luminaire with wide range of wattage and optics. Housing: heatsink made of extruded aluminum, assembly and mounting elements made of steel. Secondary optics - PMMA/PC. Tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°, step of 7,5°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Outdoor areas. Industrial facilities. Warehouses and fire hazardous zones classified as P-IIa according to Electrical Installations Regulations. Input voltage (AC, 50Hz), V: 100...305 AC frequency, Hz: 50 Input voltage (DC), V: 130...300 Flicker, %: 5 Climatic modification and category of placement: УХЛ2 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK08 Power factor: 0,95 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/olymp-gl-2-0/olymp-gl-2-0-250-vt/svetodiodnyy-svetilnik-varton-promyshlennyy-olymp-gl-2-0-250-vt-5000-k-klass-zashchity-ip65-plafon-r/

Light output 1



1 x LED

Nominal lamp power	250 W	LOR	100%
Lamp flux	36250 lm	Total flux	36252 lm
Luminous efficacy	145 lm/W	Total power	250 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 21.06 in
Width: 10.94 in
Height: 6.69 in

Adjustability

Fixed

Electric

System power: 250 W

Protection

IP: 65
IK: 08