Product data sheet

ATHLON AREA LIGHT / DOUBLE SIDED 7258-M-4-658-XX

UNILAMP










ATHLON is a series of mini floodlights with wide beam asymmetrical and bi-symmetrical light distribution. It operates with High Power LED module which is attached on aluminium body as a heat sink. The Alanod Miro reflectors used in this luminaire are designed by Photopia high-end lighting engineering software. The calibrated aiming unit provides accuracy of the light distribution on the illuminated surface. The range of accessories such as ground mount spike, tree strap and pole clamping unit makes it a dynamic floodlight choice. ATHLON is suitable to light up small to medium sized objects or areas such as signage boards, ceiling, building facades, etc.

Light output 1




| - 1 | Y | I FD |
|-----|---|------|
| | ^ | LLD |

| Nominal lamp power | 25 W |
|--------------------|----------|
| _amp flux | 3010 lm |
| _uminous efficacy | 120 lm/W |
| CCT | 2700 K |
| CRI | 80 |

LOR Total flux Total power 92% 2759 lm 28 W

Light output 2



1 x LED

| Nominal lamp power | 25 W |
|--------------------|----------|
| Lamp flux | 3010 lm |
| Luminous efficacy | 120 lm/W |
| CCT | 2700 K |
| CRI | 80 |

LOR 92% Total flux 2759 lm Total power 28 W

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 9.67 in Width: 4.13 in Height: 9.23 in

Adjustability

Rotatable, Tiltable

Electric

System power: 56 W Appliance Class: I

Protection

IP: 66 IK: 07