
Product data sheet


MITO 120
052-6417017S
XAL



IP 20


MITO 120 lamp: 1x20/35/50W HIT G8,5 reflector: spot 14° luminaire housing of sheet steel, spotlight made of aluminium spotlight gimbal mounted, tiltable up to 35°

Light output 1




1 x General service incandescent lamp

Nominal lamp power	50 W	Socket	G8D.5
Lamp flux	5400 lm	LOR	73%
Luminous efficacy	71 lm/W	Total flux	3953 lm
CCT	3000 K	Total power	56 W
CRI	90		




1 x General service incandescent lamp

Nominal lamp power	35 W	Socket	G8D.5
Lamp flux	3300 lm	LOR	73%
Luminous efficacy	62 lm/W	Total flux	2416 lm
CCT	4200 K	Total power	39 W
CRI	90		




1 x General service incandescent lamp

Nominal lamp power	35 W	Socket	G8D.5
Lamp flux	3300 lm	LOR	73%
Luminous efficacy	62 lm/W	Total flux	2416 lm
CCT	3000 K	Total power	39 W
CRI	81		



1 x General service incandescent lamp

Nominal lamp power	20 W	Socket	G8D.5
Lamp flux	1800 lm	LOR	73%
Luminous efficacy	60 lm/W	Total flux	1318 lm
CCT	2980 K	Total power	22 W
CRI	85		



1 x General service incandescent lamp

Nominal lamp power	20 W	Socket	G8D.5
Lamp flux	1650 lm	LOR	73%
Luminous efficacy	55 lm/W	Total flux	1208 lm
CCT	3000 K	Total power	22 W
CRI	85		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.45 in
Width: 4.45 in
Height: 0.04 in

Adjustability

Tiltable

Electric

System power: 22-56 W
Appliance Class: I

Protection

IP: 20