

Product data sheet

MAXZ67-1200 LED 4500 840
GLAMOX




IP
67

IK
08

Light source LED Ballast Fixed output (HF). Body material & colour Housing in Aluzink or acid-proof steel with white epoxy/polyester powder coated finish. Alternatively in unpainted acid-proof steel. The diffuser is made of impact-proof polycarbonate (PC) with moulded silicone gasket and spring clips in acid-proof steel. Mounting The luminaire is supplied with fixed end brackets, triangle suspension or 2 x M8 hood nuts. Bracket for horizontal wire and revolvable bracket to be mounted on the fixed end bracket. M8 rod -, tube -, pole -, cable bridge -, side - and vibration suspension to be mounted through the M8 hood nut. M8 hood nuts with flexible CC and other special suspensions on request. Accessories Suspension kits. Connection 6 pole 6 mm² screw terminal block. Variants with 6 x 2,5 mm² through wiring. Integrated emergency light Emergency solution for 3 hour duration is available. Fixed external battery box to achieve optimal working conditions.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	4491 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	5%
		Total power	34 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 52.52 in

Width: 6.50 in

Height: 5.04 in

Adjustability

Fixed

Electric

System power: 34 W

Protection

IP: 67

IK: 08