Product data sheet

RINQ PDI 3000 HÄNGELEUCHTE 296W 2700K SCHWARZ MIKROPRISMEN DALI
445-923001326DV1
MOLTO LUCE



IP 20 IK 02

RINQ HÄNGELEUCHTE aus Aluminium, schwarz, ähnlich RAL 8005,mikroprismatische PMMA-Abdeckung für ausgezeichnete Entblendung Lichtaustritt direkt/- indirekt, UGR <19, mit Betriebsgerät, dimmbar DALI, Kabel transparent, Pendellänge 4000mm IP20

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 2 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 3 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 4 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 5 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 6 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 9 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Light output 10 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	29 W	CRI	80
Total flux	3364 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	57%
		Total power	29 W

Mounting mode

Pendant

Shape and measurements

Length: 118.11 in

Width: 118.11 in

Height: 3.94 in

Adjustability

Rotatable, Tiltable

Electric

System power: 290 W

Appliance Class: I

Protection

IP: 20

IK: 02