# Product data sheet

ARKAS II FLEX 4000K 40W ON/OFF 7215802

WESTAL










Robust D-marked industrial luminaire made of gray ABS plastic (fire-classified according to UL94-V2) and cover in opal polycarbonate. The on / off variant is equipped with an adjustable LED-unit in 3- 4- or 5000K and adjustable power in 4 positions on the driver. 60cm = 12-20W, 120cm = 25-40W 150cm = 35-60W. Also available as a DALI variant in 4000K. Comes with two 5-pole terminal blocks on each side for 3-phase connection. Dali variant has a 5-pin terminal block for power + 2-pin for DALI. Easy to open, install and maintain. Mounting on ceiling or suspended down. The luminaire is adapted for indoor and outdoor use. Suitable for lighting in more exposed environments such as, garages and dusty, damp spaces.

#### Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
40 W	CRI
5200 lm	LOR
130 lm/W	ULOR
	Total

CCT	4000 K
CRI	80
LOR	100%
ULOR	2%
Total power	40 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 49.61 in Width: 3.74 in Height: 2.95 in

# Adjustability

Fixed

# Electric

System power: 40 W Color adjustable Appliance Class: I

## Protection

IP: 65 IK: 10