


Product data sheet

CIRCULAR OUTWARD 3 RINGS (Ø1200 Ø900 Ø600)
CF4L-00X9AZOUEF
LEDSC4




LedsC4 Circular Outward 3 Rings (Ø1200 Ø900 Ø600) CF4L-00X9AZOUEFV1 Pendant for indoor use. For sideways lighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 11 Product width or diameter (mm): 1177 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 153.4W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 7.4. Photobiological risk: RG1. Real flux (lm): 12782. Real lm/W: 80. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 159. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1




1 x LED			
Nominal lamp power	69.9 W	LOR	100%
Lamp flux	6116 lm	ULOR	49%
Luminous efficacy	87 lm/W	Total flux	6117 lm
CCT	4000 K	Total power	69.9 W
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	51.4 W	LOR	100%
Lamp flux	2992 lm	ULOR	49%
Luminous efficacy	58 lm/W	Total flux	2992 lm
CCT	4000 K	Total power	51.4 W
CRI	90		

Light output 3



1 x LED			
Nominal lamp power	37.7 W	LOR	100%
Lamp flux	3674 lm	ULOR	50%
Luminous efficacy	97 lm/W	Total flux	3675 lm
CCT	4000 K	Total power	37.7 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 47.24 in
Width: 47.24 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 159 W
Appliance Class: I

Protection

IP: 20