Product data sheet

MERCMASTER LED 4000 LUMENS 3000K CCT GLASS PRISMATIC REFRACTOR NEMA TYPE V I/MLLED3WJ5

APPLETON (EMERSON EGS)














Mercmaster LED Low Profile Series Pendant/Ceiling/Wall/Stanchion Mount 3/4" NPT Hub Glass Prismatic Refractor NEMA Type V Symmetrical 3000 K CCT/80 CRI Voltage- BU-120-277V, 50/60Hz, 125-300 Vdc BH-347-480 Vac, 50/60Hz B2-24-48 Vdc Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx ec IIC Zone 21, AEx tb IIIC Class I, Zone 2, Ex ec IIC Class II, Division 1, Group E, F, G Zone 20, Group IIIC Class II, Division 2, Group F, G Class III Simultaneous Exposure Type 3R, 4, 4X IP66/IP67 IK08 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) DLC Qualified Product listed Refer to catalog for additional options

Light output 1 (integrated)



| Lamp type | LED | |
|--------------------|----------|--|
| Nominal lamp power | 38 W | |
| Total flux | 4127 lm | |
| Luminous efficacy | 109 lm/W | |
| | | |

| LED | CCT | 3000 K |
|---------|-------------|--------|
| 38 W | CRI | 80 |
| 4127 lm | LOR | 100% |
| 9 lm/W | ULOR | 7% |
| | Total power | 38 W |
| | | |

Mounting mode

Pendant, Pole top mounted, Ceiling recessed

Shape and measurements

Length: 55.55 in Width: 2.01 in Height: 2.72 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 38 W Appliance Class: I

Protection

IP: 66 IK: 08

Designation labels: CE

Explosion zone suitability: 2, 20, 21