
Product data sheet

TURIS MINI 1.1 D [3000K 6W 230VAC]
MT11115DC
L&L LUCE&LIGHT



Recessed downlight for indoor applications; recessed (ceiling); body in anodized anticorodal aluminium lega EN AW 6060, trim in sheet metal, screen in plexiglass; finishes: white, chrome; 1 multichip power LED; 6W - 230Vac; 4,5W - 24Vdc; power supply unit: included and wired (230Vac), ot included (24Vdc);includes 0,30 m cable (230Vac), includes 2x0,50 m single-core cables (24Vdc); total delivered lumens: 310 lm (3000K); diffuse optics; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP40, IP44 installed; operating temperature: 0°C +45°C; screen temperature: max 40°C (Ta 25°C); photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: II (230Vac), III (24Vdc); weight 0,15 kg; dimensions Ø44x73 mm; cut-out size Ø40 mm; dimming using a dimmable power supply unit; accessories: outer casing for solid walls WC3108

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	80
Total flux	309 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.73 in
Width: 1.73 in
Height: 0.05 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 6 W
Appliance Class: III

Protection

IP: 40