

Product data sheet


6401/522-8508-15-131
239552
STAHL



IP
66


Light Fitting for Fluorescent Lamps EXLUX 6401 2x18W Explosion protection: Gas: Ex nA IIC T4 Gc Ex nA d IIC T4 Gc Dust: Ex tb IIIC T80 °C Db Ex tc IIIC T80 °C Dc Certificates Gas: PTB 14 ATEX 2016 Gas and Dust: PTB 14 ATEX 2017 Rated voltage: AC: 220 (- 10%) ... 240 (+ 10%) V, 50 / 60 Hz, DC: 198 ... 254 V/ 1-lamp: 176 ... 264 V Ambient temperature: -30 ... +50 °C Material: Enclosure: glass fibre reinforced polyester resin Cover: Polycarbonate Troughwiring: 5 conducters

Light output 1



2 x Fluorescent lamp tubular T5

Nominal lamp power	18 W	Socket	G13
Lamp flux	1350 lm	LOR	83%
Luminous efficacy	59 lm/W	ULOR	9%
CCT	4000 K	Total flux	2251 lm
CRI	85	Total power	38 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	18 W	Socket	G13
Lamp flux	1350 lm	LOR	83%
Luminous efficacy	59 lm/W	ULOR	9%
CCT	3000 K	Total flux	2251 lm
CRI	85	Total power	38 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 27.48 in

Width: 7.23 in

Height: 5.04 in

Adjustability

Fixed

Electric

System power: 38 W

Voltage: 230 V

Ballast: ECG

Integrated Switch: In housing

Suitable for feed-through wiring

Protection

IP: 66