


Product data sheet

MARBUL RECESSED 115 2X LED GE 2700K SPOT WHITE STRUC
14222209+10216830
MODULAR




Ready-made surface solution Marbul feels both at home on the wall and ceiling, which makes it suited for use in both residential and hospitality projects. It's a perfect ready-made solution for renovation projects, thanks to the fully integrated technology in its body. Marbul recessed is characterized by a thin trim of 5mm through which 1 or 2 spheres appear to hang gently from the ceiling without any visible attachments. Flexible installation accessories such as the conbox and gypkit enable installation in concrete ceilings. Adjustability remains the same: lamp units can be rotated 360° and inclined approximately 45°.

Light output 1




1 x LED			
Nominal lamp power	6 W	LOR	85%
Lamp flux	724 lm	Total flux	619 lm
Luminous efficacy	103 lm/W	Total power	6 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	8.9 W	LOR	85%
Lamp flux	972 lm	Total flux	831 lm
Luminous efficacy	93 lm/W	Total power	8.9 W
CCT	2700 K		
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	6 W	LOR	85%
Lamp flux	724 lm	Total flux	619 lm
Luminous efficacy	103 lm/W	Total power	6 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	8.9 W	LOR	85%
Lamp flux	972 lm	Total flux	831 lm
Luminous efficacy	93 lm/W	Total power	8.9 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Height: 2.13 in
Diameter: 9.25 in
Weight: 1.78 kg

Adjustability

Free

Electric

System power: 12-17.8 W

Protection

IP: 20