

Product data sheet


MULTILUME HYDRO ROBUST LED 600X300 4000K DALI CLO
23622-402
FAGERHULT



IP
65

Installation Recessed or surface mounted. The recessed model is suitable for fixed suspended ceilings or suspended ceilings with visible T-bars. Suspension fittings in the corners, tamper-proof torx. Connection Connection in separate driver box. The driver box can be positioned next to the luminaire. Snap-in terminal block 3x1.5 mm² (when dimming 5x1.5 mm²). Version with Tunable White or Tunable White/Amber night light is connected in terminal block at the top of the luminaire. The surface mounted model has cable entries fitted with blanking grommets on the back and in each end-cap and snap-in terminal block. Design Luminaire body in extruded aluminium and enamelled sheet steel. Surface mounted model in white enamelled sheet steel (RAL 9016). Louvre Delta – microprismatic acrylic louvre (PMMA) with impact resistant PETG plastic protective glass. Dimming Tunable White / Amber night light requires 2 DALI addresses. Miscellaneous Recessed model IP 65 under suspended ceiling, IP 50 above. Surface mounted model IP 65.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	2556 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	20 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.46 in
Width: 11.65 in
Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 20 W

Protection

IP: 65