


Product data sheet

P-INF R100H LED750-930 LDO GD TL
60817811
ZUMTOBEL



LED ceiling-recessed luminaire without trim, "Stable White"; shielding angle 45°; lamp(s): LED750-930; Colour rendering Ra > 90, colour temperature 3000 K (warm white); Chromaticity tolerance (initial MacAdam): 2; total power: 9 W; Luminaire luminous flux: 765 lm, Luminaire efficacy: 85 lm/W; service life: 50000h at 95% luminous flux; includes control unit Slave luminaire for DALI control (DALI only); modular, high quality optical unit consisting of reflector and LED light chamber integrated in optimised thermal management of die-cast aluminium; smooth reflector gold colour coated, matt; reflector made of high-quality, UV-resistant polycarbonate; luminaire unit fitted quickly without tools using twist-and-lock mechanism; IP44_IP20; luminaire wired with halogen-free leads; power connection: 5-pole connector terminal, loop-in/loop-out possible; mains voltage: 220-240V / 0/50/60Hz, for use with 220V DC central battery; tool-free quick installation using antislip spring clips in ceilings of thickness 1-40mm; ceiling cutout: 100mm, recess depth: 130mm (for ceiling thicknesses 1-15mm); weight: 0.55 kg Note: UGR<19 for office applications compliant with EN12464 (depending on luminaire type) Note: Please order seating ring (planar ring) separately for installing the luminaire flush with the ceiling (see Accessories)

Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	69%
Lamp flux	1100 lm	Total flux	764 lm
Luminous efficacy	85 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.80 in
Diameter: 4.29 in
Weight: 0.6 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 9 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: II

Protection

IP: 20
Designation labels: CE, ENEC