
Product data sheet

BASIC DÉCO SUSPENDED - G3
BG3ASE-830H-D800-UW
LIGHTNET



LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with overall height of 58mm. Outer housing and Décorative reflector ring available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For surface options and combinations check Lightnet Surface Collection or Bi-Colour Selection. Recessed microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	54 W	CRI	82
Total flux	6882 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	54 W

Mounting mode

Pendant

Shape and measurements

Height: 31.50 in
Diameter: 31.50 in

Adjustability

Height adjustable

Electric

System power: 54 W

Protection