# Product data sheet


NEOS
2356-I-5-668-XX
UNILAMP



IP 66 IK 08

NEOS NEOS is a small sized high performing area light. Outstanding optical efficacy, high ambient temperature rating and a wide range of mounting accessory makes NEOS a highly competitive product. The smooth curved design eliminates accumulation of water and dust. The unobtrusive slim design is a great match for commercial and residential lighting tasks. The area light can be either equipped with a photocell, DALI-2 control or basic on-off control gear. NEOS can be equipped with mounting accessories for pole integrated mounting, pole bracket, wall and wall corner. The pole bracket is suitable for Pole diameters up to 105mm. Features: • Photocell for simple and cost effective light management • Easy spec: one luminaire part code multiple mounting options • Supreme surge protection: mains and dimming line 10kV protected • Prewired cable 2000mm

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 23 W | LOR | 88% |
| Lamp flux | 4220 lm | Total flux | 3706 lm |
| Luminous efficacy | 183 lm/W | Total power | 25 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

### Mounting mode

Wall mounted

### Shape and measurements

Length: 2.76 in
Width: 1.89 in
Height: 4.01 in

### Adjustability

Tiltable

### Electric

System power: 25 W
Controller: DALI
Appliance Class: I

### Protection

IP: 66
IK: 08