Product data sheet

DVO15-38-014 VCF RA 940

ASTZ

ДВО15-38-014 VCF RA 940 ТУ 3461-047-05014337-2011 Предназначены для общего освещения административно-общественных помещений и производственных зданий, “чистых” комнат. 220 В, 50 Гц, 36 Вт, 4000K, Ra=80, драйвер с управлением по протоколу 1-10В (PF= 0,95), IP54, УХЛ4 Световой поток светильника: 3654 лм Класс защиты от поражения электрическим током: I LxBxH=600x600x65 мм. Масса: 6 кг Корпус - листовая сталь, окрашен белой порошковой краской (сварной). Рассеиватель из защитного закалённого матированного стекла. Установка в подвесные потолочные системы Armstrong: потолки V-Clip F на пружинную Т-рейку BPC1801H и Clip-in (Q-Clip, R-Clip, S-Clip) на рейку BT-600, а также в потолки Albes AC на рейку BT-600.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35.8 W	CRI	90
Total flux	3654 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	35.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.56 in

Adjustability

Fixed

Electric

System power: 35.8 W

Appliance Class: I

Protection

IP: 54