


# Product data sheet

ELLBD 12L40  
ELEMENT  
DEXTRA




Element - 1200mm Suspended bi-directional luminaire, white powder coated steel body with low glare microprism diffuser. Can be continuous run. Options: LE3 - Lithium Emergency (333 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming B - Black Body GY - Grey Body Continuous Run options: ST - Start of Run TW - Through Wire ER - End of Run ELL COR TW - Element Adjustable Through Wire Corner ELL BLIND 1260 TW - Element Suspended Continuous Run, 1260mm, 6 pole through wire blind unit ELL BLIND 1500 TW - Element Suspended Continuous Run, 1500mm, 6 pole through wire blind unit ELL EC - Element End Cap (please specify one set per run of luminaires). ELL JOINER - Element Joining Kit (required to connect End of Run to Start of Run luminaires where new power feeds are required mid run) P414 - 3M Suspension Kit

## Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	13.4 W	CRI	80
Total flux	1674 lm	LOR	100%
Luminous efficacy	125 lm/W	ULOR	100%
		Total power	13.4 W

## Light output 2 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	15.1 W	CRI	80
Total flux	1677 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	15.1 W

## Mounting mode

Pendant

## Electric

System power: 28.5 W  
Ballast: ECG  
Appliance Class: I

### Shape and measurements

Length: 49.61 in

Width: 9.06 in

Height: 1.61 in

### Adjustability

Fixed

### Protection

IP: 20

Designation labels: CE