


Product data sheet

STREET LIGHTING
V1-S1-90660-40L05-6605050 LEVANTE YARD 50W 5000K
VARTON



LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: objects without illumination requirements. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-yard-dlya-dvora/svetodiodnyy-svetilnik-var-ton-ulichnyy-levante-yard-50-vt-kronshteyn-60-mm-5000-k-chernyy-ral9005-mu/>

Light output 1



1 x LED			
Nominal lamp power	50 W	LOR	100%
Lamp flux	6750 lm	Total flux	6750 lm
Luminous efficacy	135 lm/W	Total power	50 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Electric

System power: 50 W

Shape and measurements

Length: 23.46 in
Width: 5.35 in
Height: 3.98 in

Protection

IP: 66
IK: 03

Adjustability

Fixed