

# Product data sheet

ELN L30 OP  
ELISIAN  
DEXTRA




IP  
40



Elisian - Ø320mm, IP40 Recessed downlighter with spun aluminium housing, four point steel spring mechanism and opal diffuser. Options: E3 - Emergency control gear (433 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest STR - Reacta-Link Wireless Self test S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless Presence & daylight RLS - Reacta-Link Wireless Presence RCS - Reacta-Control Wireless, Presence

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.8 W	CRI	80
Total flux	2316 lm	LOR	100%
Luminous efficacy	117 lm/W	ULOR	4%
		Total power	19.8 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 2.56 in  
Diameter: 12.60 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 19.8 W  
Ballast: ECG

## Protection

IP: 40  
Designation labels: CE