
Product data sheet

LINEAR LIGHTING

V1-R0-10825-02OPA-4003027 X-LINE 1,50 M STAND-ALONE 30W 2700K EM 1H


VARTON



IP 40 IK 01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-1-50-m-odinochnye/svetodiodnyy-svetilnik-varton-kh-line-odinochnyy-podvesnoy-30-vt-2700-k-1499x63x100-mm-ip40-ral9003-/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3001 lm
Luminous efficacy	100 lm/W	Total power	30 W
CCT	2700 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 59.02 in

Width: 2.48 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40

IK: 01