

# Product data sheet


A90-P2 LED 15000 840 MB  
GLAMOX



IP  
65

Light source A90-P1: LED 1000 - 5000 Lumen out A90-P2: LED 10000 - 20000 Lumen Out Light source information: 4000 Kelvin, 3000K on request. CRI 80. MacAdams 3. Ballast Fixed output (HF) or DALI dimmable. Body material & colour Luminaire top in black epoxy / polyester powder coated die-casted aluminium and component housing in injection moulded black glass reinforced polycarbonate. Cooling ribs in black anodized extruded aluminium. Reflector in anodised aluminium or opal polystyrene. Skirt in black epoxy / polyester powder coated steel and diffusor in polycarbonate. Mounting Delivered with eyebolt for pendent mounting. Ceiling bracket for surface mounting can be delivered as accessories. Accessories 4 meter suspension wire Safety wire bracket Height adjuster for wire Suspension for horizontal wire Ceiling bracket Connection A90-P is supplied with pre-assembled 4 meter rubber cable without plug. Other options on request. Optics Wide beam - (WB), medium beam - (MB) and narrow beam (NB) reflector in anodised aluminium. Opal reflector in polystyrene. Reflectors have to be ordered separately.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	125 W	CRI	80
Total flux	15166 lm	LOR	100%
Luminous efficacy	121 lm/W	ULOR	84%
		Total power	125 W

## Mounting mode

Pendant

## Shape and measurements

Height: 20.98 in  
Diameter: 19.69 in

## Adjustability

Height adjustable

## Electric

System power: 125 W

## Protection

IP: 65