


Product data sheet

DKN QUADRAT
10442.002
RZB




IP
40

IK
02

Series: DKN-Quadrat, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: ~ 250 / 0 - 60 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 360, B 360, H 110 Lamp: 2 x E27 max. 75 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 69°/62°/68°/67° Unified Glare Ratio: 17,8 EEC: A++ - E

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	21 W	Socket	E27
Lamp flux	1260 lm	LOR	63%
Luminous efficacy	38 lm/W	ULOR	15%
CCT	2700 K	Total flux	1590 lm
CRI	80	Total power	42 W

Mounting mode

Wall mounted

Shape and measurements

Length: 14.17 in
Width: 14.17 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 42 W

Protection

IP: 40
IK: 02