



Product data sheet

X-LINE LED 3900 PLX E 24 830 LINE-EL / L-1687MM
19.4161.4111.24
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Luminaire dimensions: 1687 x 63 x 74 mm. Weight 4,08 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 66,66%. Beam angle: (C0-C180) / (C90-C270) - 109° / 107,2°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 2525 lm. Power of luminaire: 21,7 W. Luminaire's light efficiency: 116,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 30 (B10), 48 (B16), 43 (C10), 70 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP44. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



3 x LED			
Nominal lamp power	7.233 W	LOR	83%
Lamp flux	1263 lm	Total flux	3162 lm
Luminous efficacy	175 lm/W	Total power	21.7 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 66.42 in

Width: 2.48 in

Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 21.7 W

Appliance Class: I

Protection

IP: 44

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F