
Product data sheet

NEW TRIA® 68 DL, PHASE, AIRTIGHT
1007421+1007347
SLV




Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. A modular element is the LED MODULE, which is available with dim-to-warm technology (1800K-3000K) and different beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI>90 ensure exceptional quality. In addition, the NEW TRIA® LED MODULE impresses with its service life of L80B10@50,000h.

Light output 1



1 x LED

Nominal lamp power	2 W	LOR	100%
Lamp flux	56 lm	Total flux	56 lm
Luminous efficacy	28 lm/W	Total power	2 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.4 W	LOR	100%
Lamp flux	570 lm	Total flux	570 lm
Luminous efficacy	55 lm/W	Total power	10.4 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.25 in
Width: 3.25 in
Height: 0.14 in
Weight: 0.25 kg

Adjustability

Fixed

Electric

System power: 2-10.4 W
Controller: Dimmable 0..10V
Color adjustable
Appliance Class: II

Protection

IP: 65