

Product data sheet

MILEWIDE LED GEN2 SMALL BPP435 T25 1 XLED25-4S/827 DM52


BPP435

PHILIPS



MileWide LED gen2 - elegant, yet highly efficient and future-proof Together with Holscher Design, we have developed MileWide LED gen2, the successor to the highly popular MileWide family. Featuring a range of dedicated masts and brackets, the pure, clean design of MileWide LED gen2 integrates perfectly with today's and tomorrow's cityscape. Thanks to its advanced LED engine, and use of application-tailored optics, MileWide LED gen2 delivers outstanding quality of light and light performance, enabling significant energy savings, yet still providing perfectly uniform light on the road. MileWide LED gen2 is also ready to be paired with lighting control and software applications because it is equipped with the Philips SR (System Ready) socket. This means it can be connected to advanced software applications, such as Interact City, at any time during its lifetime. Furthermore, each luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire's lifetime.

Light output 1



1 x LED

| | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 21 W | LOR | 88% |
| Lamp flux | 2500 lm | Total flux | 2189 lm |
| Luminous efficacy | 104 lm/W | Total power | 21 W |
| CCT | 2700 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling mounted

Electric

System power: 21 W

Shape and measurements

Length: 24.02 in

Width: 10.87 in

Height: 4.33 in