

Product data sheet

FLAT POLYMERO KREIS
311612.002.1
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 98 Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2100lm System power: 29W Beam Angle: 123° Number of fittings B10A: 9 Number of fittings B16A: 15 Number of fittings C10A: 15 Number of fittings C16A: 25 Inrush current: 20A Unified Glare Ratio: 17,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	29 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	16%
		Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 29 W

Protection

IP: 40
IK: 03