Product data sheet

LINEA S LED 1760MM 8350LM 840 IP54 CN DALI (47W)
854323
LENA LIGHTING



854323 LINEA S LED 1760mm 8350lm 840 IP54 CN DALI (47W) LINEA S LED IP54 is a surface-mounted and suspended light line system, representing a new generation of lamps dedicated to LED technology. The innovative connection system and loop-through cabling enables lamps to be quickly connected to form a light line and allows flexible replacement of light modules to suit current needs. The design used allows for easy assembly and power connection. The steel body, designed from the ground up, ensures the lamp's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The high IP54 sealing rating allows the lamps to be installed in environments with increased humidity and dust. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficiency.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47 W	CRI	80
Total flux	8350 lm	LOR	100%
Luminous efficacy	178 lm/W	Total power	47 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 69.45 in
Width: 1.97 in
Height: 2.56 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 47 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 54
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F