Product data sheet

POWERVISION 1 SURFACE HIGH BAY LUMINAIRES PW19-GP028-EW-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	26.9 W	CRI	80
Total flux	3522 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	26.9 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 18.90 in Width: 11.22 in Height: 11.81 in Weight: 9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 26.9 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66 IK: 07

Surface temperature: 40°C