


# Product data sheet

CIRCULAR DOWNWARD Ø3000 RECESSED  
CS5D-00A9AZOUEF  
LEDSC4



LedsC4 Circular Downward ø3000 Recessed CS5D-00A9AZOUEFV1 Pendant for indoor use. For downlighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 18 Product width or diameter (mm): 3016 Product height (mm): 5000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 158W. Colour temperature: 2400K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 10.0. Photobiological risk: RG0. Real flux (lm): 9935. Real lm/W: 57. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 174. Power factor: 0.90. Dimmable equipment included: ON-OFF.

## Light output 1



1 x LED			
Nominal lamp power	174 W	LOR	100%
Lamp flux	9935 lm	Total flux	9935 lm
Luminous efficacy	57 lm/W	Total power	174 W
CCT	2400 K		
CRI	90		

## Mounting mode

Pendant, Table luminaire

## Shape and measurements

Length: 118.11 in  
Width: 118.11 in  
Height: 1.77 in

## Adjustability

Fixed

## Electric

System power: 174 W  
Appliance Class: I

## Protection

IP: 20