# Product data sheet

CEILING AND WALL MOUNTED LUMINAIRE TORINO ROUND L1 24W 3200 2004.3862 - TORINO CW450 LED3200-840 DID DALI E3H

REGENT








Ceiling and wall mounted luminaire Torino round, with LED, system power: 24 W, standby power 0.5 W, luminous flux of luminaire 3200 lm, colour rendering index CRI > 80, 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, (85%/15%), opal, 1 integral control gear, DALI, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0283), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, this product contains a light source of energy efficiency class A and EPREL registration number: 1249133 Ø = 450 mm. H = 102 mm

### Light output 1



1	Х	LED

L

Nominal lamp power	22 W	
amp flux	3200 lm	
uminous efficacy	145 lm/W	
CCT	4000 K	
CRI	80	

LOR	100%
ULOR	16%
Total flux	3202 lm
Total power	24 W

# Mounting mode

Ceiling mounted

# Shape and measurements

Length: 20.47 in Width: 20.47 in Height: 3.78 in Weight: 4.373 kg

## Adjustability

Fixed

### Design

Color of housing: White

#### Electric

System power: 24 W Appliance Class: I

## Protection

IP: 40