


Product data sheet

PRELUDE WHITE W/ OUTLET 1020LM 2700K RA>90 TRAILING EDGE DIMMING
7021981113414
SG ARMATUREN



Mirror luminaire made of aluminium with diffuser made of Acrylic (PMMA). Can be installed with either concealed or visible cable. Design: Hallvard Jakobsen Light distribution Direct Light technic LED 14W 2700K Ra>90 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05 Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Acrylic (PMMA) Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 23, B16: 37, C10: 29, C16: 46

Light output 1



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1020 lm	ULOR	25%
Luminous efficacy	73 lm/W	Total flux	1020 lm
CCT	2700 K	Total power	14 W
CRI	90		

Mounting mode

Wall mounted

Shape and measurements

Length: 22.05 in

Width: 3.15 in

Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14 W

Appliance Class: I

Protection

IP: 20

IK: 05