Product data sheet

SIDELITE ECO
672191.002.1
RZB



IP 20

Item Number: 672191.002.1 Series: Sidelite ECO Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Frame: white powder coated aluminium. Diffuser: plastic (PMMA) opal, diffuser and light guide made of non-yellowing PMMA, lateral light emission with LED, lamp (LED) included, external converter (height 32mm), springs for ceiling installation included in the canopy as standard. With single battery system in combined non-maintained power mode, with integrated self-test system and status display on the luminaire. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 622, B 622, H 44mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 8h Emergency Lighting System: automatic self-test Safety Marks: F-mark Luminaire flux LED: 3700lm System power: 34W Beam Angle: 120° Number of fittings B10A: 17 Number of fittings B16A: 28 Number of fittings C10A: 29 Number of fittings C16A: 47 Inrush current: 17A Unified Glare Ratio: 21,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	3700 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	34 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.49 in
Width: 24.49 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 34 W

Protection

IP: 20