
Product data sheet

GUELL 2+ A40/W 74W 840 GR-94 DALI + VISOR
LTF1222DA840_LTF1A3252
PERFORMANCE IN LIGHTING



Part number: LTF1222DA840. Serie: GUELL. LED floodlight for indoor and outdoor, comprising: Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944. ISO 9223 (C5) . Extra clear, toughened, flat glass diffuser. High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99). Anti-ageing custom moulded silicone sealing gasket(s). M20x1.5 cable gland for cables Ø10Ø14 mm. DALI dimmable. Stainless steel locking hardware. Fully integrated stainless steel aluminium spring clips. Powder-coated steel tiltable bracket. Openable and maintainable luminaire (future-proof). Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory. Design by GIORGIO LODI. Product data | ETIM Group: EG000027. ETIM Class: EC001744. General information | Lampholder: LED. Lightsource lumen output [lm]: 12391. Luminaire lumen output [lm]: 10635. Luminaire wattage [W]: 74 W. Luminous efficacy [lm/W]: 144. CRI: 80. Colour temperature [K]: 4000. Colour / Finishing: GR-94 / Metallic grey / Textured. IP degree of protection: IP66. IK07 3J xx5. Protection class: I. Optic: A40/W - Asymmetric Wide. Net weight [kg]: 2.934. Overall length [mm]: 380. Overall width [mm]: 305. Overall height [mm]: 80. Mechanical features | Shape: Rectangular. Housing material: Aluminium. Diffuser material: Glass. Glow wire test [°C]: 650 °C. Frontal exposed area [m²]: 0.03. Lateral exposed area [m²]: 0.02. Top exposed area [m²]: 0.1. Electrical features | Voltage type: AC. Input voltage [V AC]: 220/240. Input frequency [Hz]: 50/60. Power factor / COS Φ: 0.9. Inrush current [A/µs]: 40 / 400. C10 1.5 mm²: 7. C16 2.5 mm²: 12. B10 1.5 mm²: 4. B16 2.5 mm²: 7. Dimmable DALI. Installation | Application area: PROFESSIONAL OUTDOOR. Mounting type: Floodlighting. Min. ambient temperature [°C]: -20. Max. ambient temperature [°C]: 35. Min. distance from lighted object [m]: 0.10. Installation without tools. Light features | Lamps: 1. ILCOS: DSR. MacAdam: 3. Lumen maintenance: L80B10@160000h. Distribution of light emission: Direct. Luminous Intensity Class: G*6. Zero light pollution (ULR = 0%). CIE flux code n.3 95. IPEA* (road lighting): A8+. IPEA* (large areas, roundabouts): A9+. IPEA* (cycle-pedestrian): A6+. IPEA* (green areas): A6+. IPEA* (historic city centers): A12+. Certifications | CE certified. ENEC certified. EAC certified. UKCA certified. RCM certified. Mountable on normally inflammable surfaces.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	74 W	CRI	80
Total flux	10200 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	74 W

Mounting mode

Wall mounted

Shape and measurements

Length: 14.45 in
Width: 4.21 in
Height: 1.18 in

Electric

System power: 74 W
Appliance Class: 0

Protection

IP: 66
IK: 07
Designation labels: CE, ENEC, F

Adjustability

Tiltable