## Product data sheet

VOLKMAR III (WALL FITTING) 9.840.0089.00

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure mercury v	apour lamp
Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	19 lm/W
CCT	3400 k
CRI	54

LOR	55%
ULOR	15%
Total flux	1092 lm
Total power	59 W



r x High pressure mercury vapour lamp						
Nominal lamp power	80 W	LOR	55%			
Lamp flux	4000 lm	ULOR	15%			
Luminous efficacy	25 lm/W	Total flux	2185 lm			
CCT	3400 K	Total power	89 W			
CRI	54					

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 59-89 W

Protection

IP: 55