## Product data sheet


LUCAS III (WALL FITTING BEADED) 9.837.2152.16 LEIPZIGER LEUCHTEN



IP 55


Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium	n vapour lamp	)
--------------------------	---------------	---

Nominal lamp power	50 W	LOR	83%
Lamp flux	3500 lm	ULOR	2%
Luminous efficacy	47 lm/W	Total flux	2901 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High	pressure sodium	vapour	lamp	

5 1			
Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	2%
Luminous efficacy	56 lm/W	Total flux	4642 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode	Electric
Wall mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 22.44 in	IP: 55
Diameter: 22.44 in	