# Product data sheet

PN3MR SERIES
PN3MR-E3AASRC-37MR16_IR_SP10-0
COOPER LIGHTING



IP 47

Lamps and optical elements can be changed for different distributions, Hot aiming rotates 365°, tilts 45° and locks in position without tools, Translating center beam optics provides full light output from 0 - 45°, Toroidal transformer provides full light output and very low noise, Plaster lip with direction marks accommodates ceilings 1/2 to 1" thick, Setscrews integral to bar hanger receivers provide positive locking, Bar hangers adjust up to 24" and have integral nail and tee grid clip, Junction box has (3) 1/2" pry-outs & suitable for (4) #12 thru-branch, cULus listed, Non-IC rated, thermally protected and ASTM-E283 airtight

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 37 W | LOR | 55% |
| Lamp flux | 900 lm | Total flux | 498 lm |
| Luminous efficacy | 24 lm/W | Total power | 37 W |
| CCT | 3000 K | | |
| CRI | 100 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.39 in
Diameter: 3.94 in

### Adjustability

Fixed

### Electric

System power: 37 W

### Protection

IP: 47