Product data sheet

TEMPLED RAYFIELD V3 1800 - 15 3000K
368613
TEMPLED



IP 66 IK 08

LED-Hochleistungs-Flutlichtsystem, modularer Gesamtaufbau mit austauschbaren Komponenten (Netzteile, LED-Lichtfelder, Lichtlenkungsoptiken, Abdeckscheiben), abnehmbare und getrennt installierbare Netzteilbox, Leistungsaufnahme: 1.800 Watt inkl. 3 Vorschaltgeräten, Lichtstrom: ca. 234.000 Lumen, Farbtemperatur: 3.000 K, Abstrahlwinkel: 15 Grad, Hochleistungslichtlenkungsoptiken, Schutzart: IP66, DALI-Dimmung optional, Hochvoltausführung optional, 5 Jahre Garantie, 10 Jahre Ersatzteilgarantie, Eingangsspannung AC: 100-240 VAC - 50/60 Hz, Eingangsspannung DC: 127-250 VDC, weitere Daten gemäß Produktblatt.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1800 W	CRI	70
Total flux	234000 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	1800 W

Mounting mode

Ceiling mounted, Floor mounted

Shape and measurements

Length: 26.54 in
Width: 22.80 in
Height: 21.46 in

Design

Color of housing: Silver gray

Electric

System power: 1800 W
Appliance Class: I

Protection

IP: 66
IK: 08

Other operating numbers

Ambient temperature range: -40...122°F