


# Product data sheet

LTUB60 SUT 1680 3000 NW OPAL WH  
L61ST168MOOP940NW  
LAMP



Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

## Light output 1



1 x LED			
Nominal lamp power	33.8 W	LOR	100%
Lamp flux	3189 lm	Total flux	3188 lm
Luminous efficacy	94 lm/W	Total power	33.8 W
CCT	4000 K		
CRI	90		

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 68.03 in  
Width: 2.76 in  
Height: 2.56 in

## Adjustability

Fixed

## Design

Color of housing: Black, White

## Electric

System power: 33.8 W  
Appliance Class: I

## Protection

IP: 20  
IK: 07