


Product data sheet

ETC140-GB [M] VA:IP67:LED-24/24W/3K
185-2600
WE-EF



IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. Cable gland with spiral cable bending protection. Integral EC electronic converter in thermally separated compartment. 'No tool' removable gear/lens tray. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Gimbal mounted, 360° rotatable and 30° tiltable. The optional installation blackout is recommended for mounting. To be ordered separately. Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request.

Light output 1



24 x LED			
Nominal lamp power	1 W	LOR	69%
Lamp flux	155 lm	Total flux	2571 lm
Luminous efficacy	97 lm/W	Total power	26.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Height: 12.40 in
Diameter: 11.81 in
Weight: 10.6 kg

Electric

System power: 26.5 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 67