


Product data sheet

SMART CAKE 160 IP55 LED GE 4000K MEDIUM BLACK STRUC
13004532
MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


Light output 1




1 x LED			
Nominal lamp power	36.3 W	LOR	78%
Lamp flux	4427 lm	Total flux	3443 lm
Luminous efficacy	95 lm/W	Total power	36.3 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	49.7 W	LOR	78%
Lamp flux	5725 lm	Total flux	4453 lm
Luminous efficacy	90 lm/W	Total power	49.7 W
CCT	4000 K		
CRI	90		




1 x LED			
Nominal lamp power	16 W	LOR	78%
Lamp flux	2265 lm	Total flux	1762 lm
Luminous efficacy	110 lm/W	Total power	16 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	23.5 W	LOR	78%
Lamp flux	3084 lm	Total flux	2399 lm
Luminous efficacy	102 lm/W	Total power	23.5 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	30.8 W	LOR	78%
Lamp flux	3828 lm	Total flux	2977 lm
Luminous efficacy	97 lm/W	Total power	30.8 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	42 W	LOR	78%
Lamp flux	4972 lm	Total flux	3867 lm
Luminous efficacy	92 lm/W	Total power	42 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W

Appliance Class: II

Protection

IP: 55