Product data sheet


VEKTOR BAS X 3/4/6,5K ÖK
E7220716
CARDI



IP 44 IK 06


Vektor Bas är en allmänljusarmatur IP44 med ställbar färgtemperatur 3000K/4000K/6500K och ställbart ljusflöde. Stomme av vitlackerat stål, gavlar av vit biobaserad plast, kupa av återvunnen frostad linjeprismatisk akryl ≥ 20%. Monteras dikt tak, lina, på vägg eller konsol. Armaturen är D-märkt. Kabelinföring Ø 20 mm i vardera gavel. Insticksplint i vardera gavel 5x2x2,5mm². Överkopplad. Vektor Bas har ställbart ljusflöde via dip-switchar direkt på drivdonet, se lumentabell under bilden eller längre ned på produktsidan alt. montageanvisning.

Light output 1




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2840 lm	ULOR	7%
Luminous efficacy	142 lm/W	Total flux	2840 lm
CCT	4000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	11 W	LOR	100%
Lamp flux	1560 lm	ULOR	7%
Luminous efficacy	142 lm/W	Total flux	1560 lm
CCT	6500 K	Total power	11 W
CRI	80		




1 x LED

Nominal lamp power	11 W	LOR	100%
Lamp flux	1540 lm	ULOR	7%
Luminous efficacy	140 lm/W	Total flux	1540 lm
CCT	4000 K	Total power	11 W
CRI	80		




1 x LED

Nominal lamp power	11 W	LOR	100%
Lamp flux	1460 lm	ULOR	7%
Luminous efficacy	133 lm/W	Total flux	1460 lm
CCT	3000 K	Total power	11 W
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2600 lm	ULOR	7%
Luminous efficacy	130 lm/W	Total flux	2600 lm
CCT	3000 K	Total power	20 W
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2800 lm	ULOR	7%
Luminous efficacy	140 lm/W	Total flux	2800 lm
CCT	6500 K	Total power	20 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.60 in
Width: 6.41 in
Height: 1.42 in

Adjustability

Fixed

Electric

System power: 11-20 W
Appliance Class: I

Protection

IP: 44
IK: 06