Product data sheet

PAULA VI 9.646.2056.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| 1 x High pressure sodium vapour lamp | | |
|--------------------------------------|----------|--|
| Nominal lamp power | 100 W | |
| Lamp flux | 10400 lm | |
| Luminous efficacy | 75 lm/W | |
| CCT | 2000 k | |
| CRI | 25 | |

| LOR | 83% |
|-------------|---------|
| Total flux | 8643 lm |
| Total power | 115 W |
| | |



| 1 x High pressure sodium vapour lamp | | | |
|--------------------------------------|---------|-------------|--|
| Nominal lamp power | 70 W | LOR | |
| Lamp flux | 5600 lm | Total flux | |
| Luminous efficacy | 56 lm/W | Total power | |
| CCT | 2000 K | | |
| CRI | 25 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in Electric

System power: 83-115 W

Protection

IP: 55

83% 4654 lm 83 W